

SERRE TETE ANTI BRUIT
REFERENCE: 1ST.040220
NORME: EN352-1

| | |
|------------------------|----------------------------|
| REGION | EMEA/AUS |
| POIDS | 227g |
| CONDITIONNEMENT | 1/ BOITE |
| SPECIFICATIONS | |
| ARTICLE | VeriShield Passive, VS120F |



| POS. | PART LISTING | MATERIAL | COLOR |
|------|--------------|---------------|------------|
| 1 | Ear Cup | ABS | NCS 8500-N |
| 2 | Rim | PP | NCS 8500-N |
| 3 | O-ring | Silicon | NATURAL |
| 4 | Foam Insert | PU foam | PMS 7621C |
| 5 | Ear Cushion | PVC/PU Foam | NCS 9000-N |
| 6 | Wire Guide | POM | NCS 9000-N |
| 7 | Headband | PU/Foam/Steel | NCS 9000-N |

SNR

VeriShield™ VS120F Passive Earmuff is tested according to EN 352-1:2002 at Michael & Associates Inc.

| Frequency Hz | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 | SNR |
|------------------------|------|------|------|------|------|------|------|-------|
| Mean Value, dB | 21.9 | 23.0 | 29.7 | 36.7 | 39.3 | 37.6 | 39.0 | |
| Standard Deviation, dB | 2.8 | 2.8 | 3.3 | 3.9 | 2.9 | 2.7 | 3.9 | 32 dB |
| Assumed Protection, dB | 19.1 | 20.3 | 26.3 | 32.8 | 36.4 | 34.9 | 35.2 | |

H=36 dB M=29 dB L=24 dB

SLC80

VeriShield™ VS120F Passive Earmuff is tested according to AS/NZS 1270:2002 at Michael & Associates Inc.

| Frequency Hz | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 | SLC80 |
|------------------------------|------|------|------|------|------|------|------|-------|
| Mean Attenuation, dB | 20.3 | 21.3 | 28.8 | 35.9 | 38.8 | 36.7 | 39.7 | |
| Standard Deviation, dB | 4.0 | 4.2 | 3.6 | 2.9 | 2.7 | 2.5 | 2.7 | 31 dB |
| Mean-Minus-Std Deviation, dB | 16.3 | 17.1 | 25.2 | 33.0 | 36.1 | 34.2 | 37.0 | |

Class 5

PROTECTHOMS

13 rue Jules Hermann, ZI chaudron

97490 Sainte-Clotilde

tel: 0262 58 00 14

fax: 0262 58 07 42

email: protecthoms.reunion@protecthoms.com